



POWER SPECIFICATIONS (EACH CHARGING UNIT)	
INPUT POWER CONNECTION	208-240VAC, 30A, SINGLE PHASE, 60HZ
FEEDER CIRCUIT BREAKER	LINE 1, LINE 2, AND GROUND 2-POLE, 40A, NON-GFCI TYPE
OUTPUT POWER	208-240VAC, 30A

PHYSICAL SPECIFICATIONS	
ENCLOSURE TYPE	TYPE 3R
ENCLOSURE MOUNTING	PEDESTAL
CABLE TYPE	SAE J1772
CABLE LENGTH	18 FT (5.5M)
CABLE MANAGEMENT	NON-RETRACTABLE, INTEGRAL WITH THE ENCLOSURE
UNIT OPTIONS	SINGLE UNIT (PEDESTAL-MOUNT)

USER INTERFACE	
POWER AVAILABLE	STATUS INDICATOR
CHARGING	BLINKING BLUE INDICATOR
SYSTEM DETECTED FAULT	RED STATUS INDICATOR

AUTHENTICATION	
TYPE	NON-NETWORKED RFID AUTHENTICATION CARD
PROGRAMMING	RADIO FREQUENCY REMOTE CONTROL

PROTECTION	
GROUND FAULT PROTECTION	INTEGRAL, CGID, 20mA, AUTO RESET
GROUND FAULT PROTECTION SYSTEM TEST	AUTOMATIC AT THE BEGINNING OF EACH CHARGE CYCLE

ENVIRONMENTAL	
OPERATING TEMPERATURE	-22F TO 131F (-30C TO 55C)
ELECTRO-STATIC DISCHARGE	15 KV OPEN AIR, 8 KV CONTACT
SURGE	6 KV
RADIATED IMMUNITY	20 V/M
CONDUCTED IMMUNITY	20 V
ELECTRICAL FAST TRANSIENT/BURST (EFTB)	2 KV
EMISSIONS	FCC CLASS B

STANDARDS COMPLIANCE	
NEC ARTICLE	625
SAE	J1772
UL	UL2594, UL2231-1 & UL2231-2, UL991, UL1998 AND UL2251

DUAL DIMENSIONS: MILLIMETER
INCHES

CATALOG NUMBER	OUTPUT VOLTAGE SYSTEM	OUTPUT CURRENT	MOUNTING TYPE	CHARGING UNIT	APPLICATION	AUTHENTICATION
EV230PSR	208-240VAC	30A	PEDESTAL	SINGLE	OUTDOOR	-

EVLINK SINGLE PEDESTAL
30A OUTDOOR CHARGING STATION

DWG# EV230PSR
NO.

